

X AGRO

it helps to grow



PROFESSIONAL MACHINERY SYSTEMS
....FOR AGRICULTURE WORLD !



अन्नदाता सुधी भवः

MACHINERY CATALOG

Agriculture

XAGRO WP 15



Rated Power	1.8kW (2.5HP)
Displacement	98 cc
Speed	3600 RPM
Engine Type	4 Stroke Air Cooled
Oil Capacity	400ml
Fuel Used	Petrol
Starting System	Recoil Started
Max. Output Discharge	200 LPM
Pump Head	16 m
Fuel Tank Capacity	1.3 Ltr.

XAGRO WP 20



Rated Power	4.4 kW (6HP)
Displacement	212 cc
Speed	3600 RPM
Engine Type	4 Stroke Air Cooled
Oil Capacity	600ml
Fuel Used	Petrol
Starting System	Recoil Started
Max. Output Discharge	500 LPM
Pump Head	24 m
Fuel Tank Capacity	3.6 Ltr.

XAGRO WP 30



Rated Power	4.4 kW (6HP)
Displacement	212 cc
Speed	3600 RPM
Engine Type	4 Stroke Air Cooled, OHV
Oil Capacity	600ml
Fuel Used	Petrol
Starting System	Recoil Started
Max. Output Discharge	750 LPM
Pump Head	25 m
Fuel Tank Capacity	3.6 Ltr.

HTP

Model	Motor Rated Power	Pump Speed	Pressure	Output	Pump Head	Pump Ball Cock Size
HTP22	1.5-2 HP	800-1200RPM	20-45 kg/cm2	14-22 L/min	Cast Iron	8.5mm (1/4) 2cocks
HTP30	3-5 HP	800-1000RPM	20-45 kg/cm2	33-40 L/min	Cast Iron	10mm (1/2) 3cocks
HTP50	3-5 HP	800-1000RPM	20-45 kg/cm2	45-65 L/min	Cast Iron	10mm (1/2) 3cocks
HTP80	5-7 HP	800-1000RPM	20-45 kg/cm2	55-85 L/min	Cast Iron	10mm (1/2) 3cocks
HTP120	7-9 HP	800-1000RPM	20-45 kg/cm2	103-116 L/min	Cast Iron	10mm (1/2) 3cocks



HTP22



HTP30



HTP50



HTP80



HTP120

XAGRO 4S-PPS35



Engine Type	4 Stroke, Petrol
Displacement	35 cc
Rated Power	1 kW (1.2HP)
Engine Speed	7000 RPM
Working Pressure	10-40 kg-cm2
Liquid Output	3-8 L / min
Fuel Consumption	550 ml / Hr
Fuel Tank Capacity	600ml
Carburetor Type	Diaphragm-Type
Accessories	15 Meter Hope Pipe and Gun.

XAGRO 4S-BC35



BACK PACK



SIDE PACK

Rated Power	1.0kW (1.4HP)
Displacement	35.8 cc
Speed	7800 RPM
Engine Type	4 Stroke Air Cooled ¹
Fuel Used	Petrol
Fuel Tank Capacity	1 Ltr.
Extra	3 Point Blade. Circular Saw Blade. Tap and Go. Paddy Guard.



ATTACHMENT

XAGRO-BC 35 / ST

Rated Power	1.0 kW (1.4HP)
Displacement	35.8 cc
Engine Type	4 Stroke Air Cooled ¹
Speed	7800 RPM
Fuel Tank Capacity	1 Ltr.
Fuel Consumption	1 Ltr. / Hr
Fuel Used	Petrol

Extra : 3T Blade.
Circular Saw Blade.
Tap and Go.



**BRUSH CUTTER
STAND TYPE**





BRUSH CUTTER

HONDA GX 35 BC-35 SP

POWERED by
HONDA

Rated Power	1.0 kW (1.3 HP)
Displacement	35.8 cc
Engine Type	4 Stroke, Air Cooled
Speed	7000 RPM
Fuel Tank Capacity	0.63 Ltr.
Fuel Consumption	0.7 L / hr
Fuel Used	Petrol
Extra	3 Point Blade, Circular. Saw Blade , Tap and Go.



ENGINE MODEL HONDA GX 35

POWERED by
HONDA

PPS-35X



Engine Type	4 Stroke, Petrol
Displacement	35 cc
Rated Power	1 kW (1.2HP)
Engine Speed	7000 RPM
Working Pressure	10-40 kg-cm2
Liquid Output	3-8 L / min
Fuel Consumption	550 ml / Hr
Fuel Tank Capacity	600ml
Carburetor Type	Diaphragm-Type
Accessories	15 Meter Hope Pipe and Gun.





HTP COMPLETE SET



GUNS

MODEL NO.

Rated Power
Displacement
Speed
Engine Type
Fuel Used
Starting System
Fuel Tank Capacity
Oil Capacity
Pump Speed
Output Pressure
Suction Volume
Pump Head
Pump Ball Cock Size
Set

HTP 22-X200

4.4 kW (6HP)
212 cc
3600 RPM
4 Stroke, Air Cooled OHV
Petrol
Recoil Started
3.6 Ltr.
600 ml.
800-1200 RPM
10-22 kg / cm ²
10-22 L / min
Cast Iron
8.5 (1/4) 2 cocks
HTP, Engine, Frame Belt, Pulley, Hose, Gun

HTP 30-X200

4.4 kW (6HP)
212 cc
3600 RPM
4 Stroke, Air Cooled OHV
Petrol
Recoil Started
3.6 Ltr.
600 ml.
800-1200 RPM
10-40 kg / cm ²
30-40 L / min
Cast Iron
10 (1/2) 3 cocks
HTP, Engine, Frame Belt, Pulley, Hose, Gun



HTP COMPLETE SET

POWERED by
HONDA



ENGINE MODEL NO.: HONDA GX160

Rated Power	3.6 kW (4.8 HP)
Displacement	163 cc
Speed	3600 RPM
Engine Type	4 Stroke, Air Cooled OHV
Fuel Used	Petrol
Starting System	Recoil Started
Fuel Tank Capacity	3.1 Ltr.
Oil Capacity	600 mL.
Engine Rated Power	3-4.5 Hp
Pump Speed	800-1200 RPM
Output Pressure	10-22 kg / cm ²
Suction Volume	10-22 L / min
Pump Head	Cast Iron
Pump Ball Cock Size	8.5 mm (1/4) 2 cocks

HONDA GX200

Rated Power	4.1 kW (4.8 HP)
Displacement	196 cc
Speed	3600 RPM
Engine Type	4 Stroke, Air Cooled OHV
Fuel Used	Petrol
Starting System	Recoil Started
Fuel Tank Capacity	3.1 Ltr.
Oil Capacity	600 mL.
Engine Rated Power	4-5.5 Hp
Pump Speed	800-1200 RPM
Output Pressure	10-40 kg / cm ²
Suction Volume	30-40 L / min
Pump Head	Cast Iron
Pump Ball Cock Size	10 mm (1/2) 3 cocks



CHAINSAW

Model No.	XAGRO CS 45	XAGRO CS 58
Engine Power	1.7kW	2.5kW
Displacement	45cc	58cc
Engine Type	2 Stroke , Air Cooled	2 Stroke , Air Cooled
Speed	3000-3200 RPM	3000-3200 RPM
Fuel Tank Capacity	550ML. Petrol	550ML. Petrol
Bar Length	18 inches	22 inches



SPRAY HOSE PIPE JAPANESE TECHNOLOGY

Inner Diameter	Thickness	Working Pressure	Bursting Pressure	Connector Type	Connector Size	Length
8.5mm	2.5-3mm	60kg/cm ²	150kg/cm ²	Male-Femal	1/4 Joint	50Mtr./100Mtr.
10mm	2.5-3mm	60kg/cm ²	120kg/cm ²	Male-Femal	1/2 Joint	50Mtr./100Mtr.
13mm	2.5-3mm	60kg/cm ²	90kg/cm ²	Male-Femal	-	100Mtr.



EARTH AUGER

Model No.	XAGRP 2S-EA52	XAGRP 2S-EA63
Displacement	51.7 cc	63.3 cc
Engine Type	2 Stroke, Air Cooled	2 Stroke, Air Cooled
Fuel Tank Capacity	800 ml	800 ml
Fuel Consumption	600 ml / hr	600 ml / hr
Speed	2800 RPM	2800 RPM
Output Performance	50-60 Pits / hr	50-60 Pits / hr
Fuel Used	Petrol	Petrol



KNAPSACK POWER SPRAYER

XAGRO 4S-4SKP26

XAGRO 4S-4SKP35

Engine Type	2 Stroke, Petrol	4 Stroke, Petrol
Displacement	25 cc	35 cc
Rated Power	0.7 kW (0.94HP)	1 kW (1.2HP)
Plunger Die	18 mm	18 mm
Pressure	25 -30 kg-cm2	25 -30 kg-cm2
Chemical Tank	25 Ltr.	25 Ltr.
Out Put	8 L / Min	8 L / Min
Fuel Consumption	550 ml / Hr	550 ml / Hr
Fuel Tank Capacity	650ml	600ml



SELF PROPELLED REAPER

XAGRO-6GPW

Engine Type	4 Stroke, Single Cylinder, Air Cooled
Engine Speed	3600 RPM
Fuel Type	Petrol
Displacement	208 cc
Engine Power	4 kW (6.0 HP)
Fuel Tank Capacity	3.6 Ltr.
Fuel Consumption	750 ml / h
Starting Method	Recoil Start
Cutting Height and Width	50 mm / 1200mm
Cutting Height Adjustment	4-22 inches.



XAGRO-6GPW

Rated Power	4.4 kW (6HP)
Displacement	212 cc
Engine Speed	3600 RPM
Weeder Type	Gear Drive
Cultivation Width - Depth	114-125 cm / 6.5cm
Number of Gears	2 Forward and 1 Reverse
Blade Set	32 Blade
Fuel Consumption	0.9 ltr. / hr
Fuel Tank Capacity	3.6 Ltr. Petrol



POWER WEEDER

Input Output
1/2 PHASE **50/60** Hz **220V/380V** **DC**

KEY FEATURES

- 1 Multi Card IGBT Inverter Machine
- 2 Single / Double Phase
- 3 VRD FUNCTION
- 4 ARC Force
- 5 Anti Stick
- 6 Generator Compatible



MMA 225 I



MMA 260 II



MMA 300 I



MMA 300 II



MMA 325 II



MMA 425 II



MMA 400



MMA 400 H

ELECTRIC



X WHEELS

ELECTRIC SCOOTER



SHINE OUT THE BEST

MFG. By:

metis CORPORATION

Ⓜ E-16, SMA Co-operative, Industrial Area, near Jahangirpuri Metro, New Delhi-33

HELP LINE 011 45136408 • +91 95828 91995

E-mail: metiscorpn@gmail.com • info@xagro.in

Website : www.xagro.in

